

Docket: 7002/3
US Pat. Appln. No.10/511,404

RECEIVED
CENTRAL FAX CENTER
DEC 13 2006

IN THE CLAIMS:

Please Cancel Claims 9 and 10 without prejudice and without disclaimer of subject matter.

Please Amend Claims 1, 3 and 4 as shown.

1. (Currently Amended) A self-tightening keyless chuck for gripping a tool shank, comprising:

- a rear sleeve (1);
- a body (2);
- a bearing ring (3);
- a bearing assembly (4);
- a nut (5);
- a jaw (6);
- a front sleeve (7); and
- a stopper (8),

wherein ~~the~~ a surface of at least one of the bearing ring (3) and the nut (5) that faces the bearing assembly (4) is provided with a recessed circumferential arcuate race (9), and a plurality of ball-shape grooves (10) are uniformly formed in an arcuate bottom surface of the arcuate race (9), and

wherein the front sleeve (7) engages with the nut (5) through radial smooth press-fit.

2. (Original) The self-tightening keyless chuck according to claim 1, wherein the nut (5) is provided with two angularly-cut split notches (11) that are symmetrically positioned on both ends of a diameter of the nut, the angularly-cut split notches (11) having a cut-out angle between 30 and 75°.

Docket: 7002/3
US Pat. Appln. No.10/511,404

3. (Currently Amended) A self-tightening keyless chuck for gripping a tool shank, comprising:

- a rear sleeve (1);
- a body (2);
- an upper bearing ring (31);
- a bearing assembly (4);
- a lower bearing ring (32);
- a nut (5);
- a jaw (6);
- a front sleeve (7); and
- a stopper (8),

wherein ~~the~~ a surface of at least one of the upper bearing ring (31) and the lower bearing ring (32) that faces the bearing assembly (4) is provided with a recessed circumferential arcuate race (9), and a plurality of ball-shape grooves (10) are uniformly formed in an arcuate bottom surface of the arcuate race (9), and

wherein the front sleeve (7) engages with the nut (5) through radial smooth press-fit.

4. (Currently Amended) The self-tightening keyless chuck according to claim 3, wherein the nut (5) is provided with two angularly-cut split notches (11) that are symmetrically positioned on both ends of a diameter of the nut, the angularly-cut split notches (11) having a cut-out angle between 30 and 75°,

and wherein two parallel cut-out surfaces (13) are symmetrically formed on ~~the~~ an outer peripheral surface of the nut (5), which extend downwards in an axial direction from ~~the~~ a front end surface of the nut (5) by one third of ~~the~~ a thickness of the nut and are located at an angle of 90° relative to the positions of angularly-cut split notches (11).

5. (Original) The self-tightening keyless chuck according to claim 1 or 3, wherein the front sleeve (7) is press cast using a press-casting metal or a powdered metallurgic material.

Docket: 7002/3

US Pat. Appln. No.10/511,404

6. (Original) The self-tightening keyless chuck according to claim 1 or 3, wherein the recessed circumferential arcuate race (9) has an arc radius R from 1.5 to 2.5 millimeters and a depth H from 0.05 to 0.30 millimeters.

7. (Original) The self-tightening keyless chuck according to claim 1 or 3, wherein the number of ball-shaped grooves (10) ranges from 20 to 80.

8. (Original) The self-tightening keyless chuck according to claim 1 or 3, wherein the ball-shaped grooves (10) have a spherical radius r from 1.0 to 2.0 millimeters and a depth h from 0.01 to 0.10 millimeters.

9. (Canceled)

10. (Canceled)